



Design Notes:

1. Depth of subbase subject to site specific hydraulic and structural requirements. Contact Belgard Commercial for design assistance.
2. Paver dimensions subject to aspect and plan ratio requirements based on traffic loading, including any maintenance and/or emergency vehicles.
3. Geotechnical engineer needs to balance structural stability and soil infiltration when recommending subgrade conditions.
4. Elevation of horizontal discharge pipe(s) subject to storage reservoir requirements. Ensure proper cover over the horizontal pipes.
5. Where the filtration geotextile is used, verify with the manufacturer that the material is not subject to clogging and meets requirements of AASHTO M-288.
6. When traffic flow is perpendicular to the direction of the header, the width of the header curb should be sufficient to ensure that a bouncing tire caused by differential settlement will land on the header and not skip over it.
7. Strictly pedestrian applications may substitute base/subbase layers with one 6" base layer of ASTM No. 57 stone.



belgardcommercial.com
877-235-4273
details@belgard.com

This drawing is for illustrative purposes only and should not be used for construction without the signature of a registered professional engineer.

Belgard Permeable Paving Detail

PICP Pavement Transition to Asphalt

Scale:	Drawn by:
N.T.S.	MAH
Date:	Drawing number:
5/7/18	PICP_7