


HAND CUT BLOCK UNITS  
TO WITHIN  $\frac{1}{2}$ " OF PIPE



SCOUR PROTECTION AS  
REQUIRED. USE RIPRAP OR  
PRECAST SLAB IN OUTLET  
AREA (DESIGNED BY OTHERS)

FACE VIEW

CAP BLOCK

DIAMOND  
PRO®<sup>A</sup>  
BLOCK

7°

12" (MIN) OF FREE-  
DRAINING AGGREGATE

GEOSYNTHETIC  
REINFORCEMENT

SCOUR  
PROTECTION

WRAP PIPE IN FILTER FABRIC TO REDUCE  
FINES WASHING OUT THE FACE

4" Ø DRAIN TILE (EL. VARIES)

6"  
2'-0"

6" MINIMUM COMPACTED  
GRANULAR-BASE LEVELING PAD

SECTION VIEW



© 2015 Anchor Wall Engineering, LLC  
© and <sup>TM</sup> Anchor Wall Systems, Inc.  
[www.anchorwall.com](http://www.anchorwall.com)

This drawing is for illustrative  
purposes only and should not be  
used for construction without the  
signature of a registered  
professional engineer.

## Diamond Pro® Beveled Face Retaining Wall System

### Typical Details for Small Utilities Through Wall

Scale:  
3/8" = 1'-0"

Drawn by:  
SB

Date:  
1/19/2016

Drawing number:  
DPBV23