



Moduline™ Series

Belgard's Moduline™ paving system was developed to create the ultimate in pattern versatility. All units are based on a true installed 3-inch or 4-inch dimensional increment and have a footprint that allows all units to fit together. All Moduline units have a micro-chamfer to minimize vibration and enhance wheelchair comfort. Additionally, the various aesthetic elements, including colors and textures, create unique patterns, accents, and borders, making the possibilities truly endless.



MODULINE PAVER SERIES		Paver Thickness	APPLICATIONS (Recommended Thickness Listed)					COLORGARD PROCESS
			COMMERCIAL Plaza	FACILITY & Business Parking	COMMERCIAL & Residential Roads	MINOR COLLECTOR & Bus Parking	ADA ²	COLORGARD ¹ Color Protection
	3" x 12"	80 mm 101.6 mm	80 mm	80 mm	101.6 mm		✓	✓
	4" x 18"	80 mm	80 mm				✓	✓
	6" x 6"	60mm 80 mm*	60 mm	80mm			✓	✓
	6" x 12"	60 mm 80 mm* 101.6 mm	60 mm	80 mm	101.6 mm	101.6 mm	✓	✓
	12" x 12"	60 mm 80 mm*	60 mm	80 mm			✓	✓
	12" x 12" ADA Truncated Dome	60 mm	60 mm				✓	✓
	12" x 18"	60 mm*	60 mm				✓	✓
	12" x 24"	60 mm*	60 mm				✓	✓
	18" x 18"	60 mm*	60 mm				✓	✓
	18" x 24"	60 mm*	60 mm				✓	✓
	24" x 24"	60 mm*	60 mm				✓	✓
	24" x 30"	60 mm*	60 mm				✓	✓

*Available as special order.

¹ Colorgard is an integral process that uses oxide pigmentation to disperse key colors homogeneously throughout each paver.


² All Moduline units are manufactured with a 3 mm chamfer width.

Solid Colors



Note: Some Moduline pavers can be used for vehicular applications. Appropriate shape and thickness is based on project-specific conditions, including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard Representative when specifying products for vehicular applications.

Blended Colors



**Light colored paver has an SRI value of ≥ 29 and/or an SR value of ≥ 0.33 .

Texture/Finishes

Belgard® provides textures and finishes to create the exact look you desire for your project.



SMOOTH

Unit surfaces and micro-chamfers are carefully molded using a high-quality precision machined steel shoe assembly which creates units with an extremely smooth surface and precision detailed chamfer.



SHOT BLAST

Exposes the surface of the paving unit to reveal the natural beauty of the aggregates and pigmentation.

Sample Moduline Patterns***

NOTE: Patterns recommended for VEHICULAR USE are highlighted in orange.

K PATTERN 2-6 x 6 (25%), 4-6 x 9 (75%) 2-12 x 12 (25%), 4-12 x 18 (75%)	HERRINGBONE 6 x 12 12 x 24	BOX PATTERN 1 1-6 x 6 (20%), 1-12 x 12 (80%) 1-12 x 12 (20%), 1-24 x 24 (80%)	BOX PATTERN 2 1-6 x 6 (14%), 1-6 x 12 (29%), 1-12 x 12 (57%) 1-12 x 12 (14%), 1-12 x 24 (29%), 1-24 x 24 (57%)	BOX PATTERN 3 1-6 x 6 (14%), 1-6 x 12 (29%), 1-12 x 12 (57%) 1-12 x 12 (14%), 1-12 x 24 (29%), 1-24 x 24 (57%)	BOX PATTERN 4 1-6 x 6 (12.5%), 1-3 x 12 (12.5%) 1-6 x 12 (25%), 1-12 x 12 (50%)

***Additional patterns are available. Please contact your sales rep or visit www.BelgardCommercial.com to view more.



BELGARD®

Anchor, An Oldcastle® Company

800 Uhler Road | Easton, PA 18040
46 Spring Street | Holbrook, MA 02343
2630 Conway Road | Odenton, MD 21113

For more info visit: BelgardCommercial.com

Get Social



[Pinterest.com/Belgard](https://www.pinterest.com/Belgard)



[Facebook.com/OutdoorLivingByBelgard](https://www.facebook.com/OutdoorLivingByBelgard)



[Belgard.com/Blog](https://www.youtube.com/BelgardHardscapes)



[YouTube.com/BelgardHardscapes](https://www.youtube.com/BelgardHardscapes)



[Twitter.com/Belgard](https://twitter.com/Belgard)



[Instagram.com/BelgardOutdoorLiving](https://www.instagram.com/BelgardOutdoorLiving)