



Design Notes:

1. Cross section as shown is suitable for pedestrian and vehicular applications. Paver dimensions subject to aspect and plan ratio requirements. Contact Belgard Commercial for product selection guidance based on the intended traffic loading.
2. Depth of aggregate base subject to site specific conditions (traffic loading, soil conditions, groundwater levels, climatic conditions). Contact Belgard Commercial for design assistance.
3. When traffic flow is perpendicular to the direction of the header, the width of the header curb should be sufficient to ensure that a bouncing tire caused by differential settlement will land on the header and not skip over it.
4. When using geotextile separation fabric, consult with the manufacturer to ensure the material has good drainage characteristics and is not prone to clogging.
5. Drain pipes may be required within the aggregate base depending on the permeability of the subgrade soils. Verify drainage needs with the geotechnical engineer. Ensure drain pipes are able to daylight via gravity flow to surface, or connect to catch basin.
6. Techniseal HP Nextgel jointing sand conforming to ASTM C144 may be used in pedestrian and light vehicular applications. Please contact Belgard Commercial for design assistance.



belgardcommercial.com

877-235-4273

details@belgard.com

This drawing is for illustrative purposes only and should not be used for construction without the signature of a registered professional engineer.

Belgard Standard Paving Detail

Asphalt to Sand Set on Concrete Base Transition

Scale:	Drawn by:
N.T.S.	PCC
Date:	Drawing number:
6/26/2020	ICP_5a