




AQUALINE™ 9" L-STONE PERMEABLE PAVER


LOW MAINTENANCE
WITH FALSE JOINTS FOR A
DURABLE, CONTEMPORARY
MULTI-PIECE LOOK

PALLET LAYOUT



FEATURES & BENEFITS

- Can eliminate stormwater runoff and improve water quality
- Interlocking spacer bars for increased structural performance
- Smooth surface texture with a micro-chamfer to minimize vibration and enhance wheelchair comfort
- Can be utilized to construct an ADA-compliant pavement
- True installed dimensions for design optimization
- Optimal joint openings for infiltration and maintenance
- Meets the requirements of ASTM C936
- False joints to provide a multi-size appearance
- L-Shape is ideal for mechanical installation and to minimize cutting
- Chamfer Width: 3 mm
- Spacer Bar Width: 10 mm
- Surface Infiltration Rate: > 500 inches per hour (varies based on joint infill gradation)
- Surface Open Area: 10%

Mechanical
Installation Available 

Contact your local Belgard® representative for details and mechanical availability.

Belgard permeable pavers can be used for a variety of different vehicular applications. Appropriate shape and thickness is based on project-specific conditions, including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard Representative when specifying products for vehicular applications.

SHAPES & SIZES

L-SHAPE



9 x 9 x 3/4