



# AQUALINE™ ASHLAR


## PERMEABLE PAVER

LOW MAINTENANCE AND PROVEN DURABILITY IN A CONTEMPORARY 3-PIECE SYSTEM


### FEATURES & BENEFITS

- Interlocking spacer bars for increased structural performance
- Smooth surface with a micro-chamfer to minimize vibration and enhance wheelchair comfort
- Can be utilized to construct an ADA-compliant pavement
- True installed dimensions for design optimization
- Optimal joint openings for infiltration and maintenance
- Can eliminate stormwater runoff and improve water quality
- Meets the requirements of ASTM C936
- Chamfer Width: 3 mm
- Spacer Bar Width: 10 mm
- Surface Infiltration Rate: > 500 inches per hour (varies based on joint infill gradation)
- Surface Open Area: 12%
- Can be installed mechanically


### PALLET LAYOUT



### LAYING PATTERNS



HERRINGBONE (MECHANICAL)  
4 1/2 X 4 1/2 (22%), 4 1/2 X 9 (25%), 9 X 9 (53%)



RUNNING BOND (MECHANICAL)  
4 1/2 X 4 1/2 (22%), 4 1/2 X 9 (25%), 9 X 9 (53%)

Mechanical Installation Available 

Contact your local Belgard® representative for details and mechanical availability.

Check with your local Belgard Representative for product availability and color options.

### SHAPES & SIZES

#### 3-PIECE ASHLAR

