



DIAMOND PRO PS

SMOOTH FACE RETAINING WALL

A REFINED, MODERN APPEARANCE WITH THE STRENGTH OF THE DIAMOND PRO RETAINING WALL SYSTEM

✓ FEATURES & BENEFITS

- Pin system installation method
- Large cores for ease in handling
- Ease of installation with oversized pin aligning cores
- Pin cores allow for multiple batter options
- Builds walls in excess of 50 feet when combined with geosynthetic reinforcement
- One square foot of wall face per block
- Gravity walls can be built up to 4 feet high*, including the buried course, with 7.1 degree batter
- Minimum outside radius, measured on the top course to the front of the units: 4 feet
- Minimum inside radius, measured on the base course to the front of the units: 6 feet
- Setback/System Batter: Near Vertical and 1"/7.1°; additional system batter can be created by alternating pin placement on each course of wall

📦 SHAPES & SIZES

BLOCK



8 x 18 x 12

ANCHOR™ PINS



5" L x 0.5" Diameter

CAP



4 x 18 / 12 x 12½

CORNER



8 x 16¾ x 7½

**Gravity wall heights are based on project specific conditions and may be lower than this value. Check with your local Belgard Representative for product availability and color options.*



For more info, visit BelgardCommercial.com

Oldcastle APG - A CRH Company
400 Perimeter Center Terrace, Suite 1000
Atlanta, GA 30346
☎ 1-844-495-8210



© 2022 Oldcastle® APG, A CRH Company. All Rights Reserved. BEL20-202 Rev: 6/16/2022