



THE "KEY" TO YOUR SUCCESS

Our unique "Adjustment Key" allows you to level and adjust our Pedestal Supports WITHOUT removing the paver. This unique feature saves labor costs and reduces possible injuries from heavy pavers



LOCKING COUPLING

Allows head to be locked into the threaded screw.



BASE PRE-CUT LINES

Base bottom with pre-cut lines for easy and precise cuts when needed for corner placement situations.



BLOCK SYSTEM

Block system indicates to installer when unit has safely reached its maximum height adjustment. A cut out is also part of this system that allows the installer to push in a safety tab, releasing components if necessary.



ADJUSTABLE PEDESTALS

SE & NM SERIES

PAVER INSTALLATION SYSTEM FOR UNLEVEL SURFACES OR FOR ALLOWING ACCESS TO UTILITIES

FEATURES & BENEFITS

- Bi-material head for increased stability and sound dampening
- Ability to raise and lower pedestals with pavers in place using adjustment key
- High load capacity
- Efficient installation



SE SUPPORT

Self-Leveling Head	✓
Fixed	✓ With the Eterno Lock fixed locking piece only
Adjustable	✓
Extension Element	✓
Adjustment Key	✓
Locking IPE Pins	✓
Recyclable (LEED)	✓
Loading Capacity	2205 LBS. (1000 KG)
Height Range	1.125" - 21.75" (28 MM - 550 MM)



NM SUPPORT

Self-Leveling Head	NA
Fixed	✓
Adjustable	✓
Extension Element	✓
Adjustment Key	✓
Locking IPE Pins	✓
Recyclable (LEED)	✓
Loading Capacity	3000 LBS. (1500 KG)
Height Range	1" - 10.63" (25 MM - 270 MM) 39" With Extensions

FEATURES	SUPPORTS
#1 Bi-Material Head	New Self-Leveling Head with Bi-Material PP & Rubber Anti-Noise & Anti-Slip
#2 Pre-Cut Tabs	Easy removal of Tabs When Needed
#3 Locking Coupling	Coupling Locks Into Head
#4 Block System	New Self-Leveling Head with Bi-Material PP & Rubber Anti-Noise & Anti-Slip
#5 Water Drainage Holes	No Ponding Water
#6 Adjustment Key	Levels Support without Removing Paver
#7 Screw	V0 3/4" (19mm) / V1 7/8" (22mm) / V2 1-1/4" (35mm) / V3 2-1/4" (60mm) / V4 4" (105mm) / V5 6" (155mm)
#8 Extension	Extension for Higher Requirements
#9 Base	B0 5/8" (16mm) / B1 7/8" (25mm) / B2 1-5/8" (40mm) / B3 2-1/2" (65mm)

Check with your local Belgard Representative for product availability.