

Cast in place concrete curb per local standards. 6" wide minimum.

2 x #4 Rebar

Topsoil Infill

Belgard Turfstone

1" Bedding Layer, conforming to ASTM C33 with maximum 1% passing the No. 200 Sieve.

Compacted Dense-graded Aggregate Base, minimum 8" thick. Asphalt or cement treatment base can be used over weak or saturated subgrade soils.

Geotextile separation fabric on entire bottom and sides of aggregate base

Base extends minimum 12" beyond grid perimeter

Compacted Subgrade. Prepare according to recommendations in the geotechnical report.

Design Notes:

1. Cross section as shown is suitable for light vehicular applications, including parking lots, emergency access or residential driveways.
2. Depth of aggregate base subject to site specific conditions (traffic loading, soil conditions, groundwater levels, climatic conditions).
3. An edge restraint for all Turfstone applications is required. Commercial vehicular applications should utilize a 6" wide concrete curb for containment.



belgard.com

877-235-4273

details@belgard.com

This drawing is for illustrative purposes only and should not be used for construction without the signature of a registered professional engineer.

Belgard Grid Paving Detail

Grid Paver (Turfstone) Used in a Vehicular Application

Scale:	Drawn by:
N.T.S.	PCC
Date:	Drawing number:
02/27/2018	GP_02