



BACKED BY  
**ANCHOR**  
DIAMOND  
INDUSTRY EXPERTS



# DIAMOND PRO<sup>®</sup> 9D

## RETAINING WALL

A LIGHTWEIGHT SOLUTION FOR  
SEGMENTAL RETAINING WALLS

### ✓ FEATURES & BENEFITS

- All system components are standard-split in-line
- Rear lip locators easily establish a uniform wall batter
- A matching cap completes the system
- Face styles available are Standard and virtual joint styles
- Gravity walls can be built up to 2.5 feet\* high, including buried course
- Taller walls can be built by incorporating geosynthetic reinforcement when designed by a qualified engineer.
- Minimum outside radius, measured on the top course to the front of the wall units: 4 feet
- Minimum inside radius, measured on the base course to the front of the wall units: 6 feet

### 🧱 SHAPES & SIZES

#### BLOCK



8 x 18 x 9

#### VIRTUAL JOINT



8 x 18 x 9

#### CAP



4 x 18 x 12

#### CORNER



8 x 18 x 9

*\*Gravity wall heights are based on project specific conditions and may be lower than this value.  
Check with your local Belgard Representative for product availability and color options.*

**BELGARD  
COMMERCIAL**

For more info, visit [BelgardCommercial.com](http://BelgardCommercial.com)

Oldcastle APG - A CRH Company  
400 Perimeter Center Terrace, Suite 1000  
Atlanta, GA 30346  
☎ 1-844-495-8210



© 2022 Oldcastle<sup>®</sup> APG, A CRH Company. All Rights Reserved.  
BEL20-202 Rev: 6/16/2022