



GEOHOLD[®]

RETAINING WALL SYSTEM

AN ECONOMICAL SOLUTION TO
MAXIMIZE INSTALLATION AND
SHIPPING EFFICIENCIES

FEATURES & BENEFITS

- Can be installed as a gravity wall or geogrid-reinforced wall.
- Weighing only 54 lbs., this 1 square foot block maximizes installation and shipping efficiencies
- Front lug design produces a 9/16" per unit setback for a 4° system batter
- Cores align for easy filling
- Cores can accommodate light fencing when combined with additional engineered elements
- Ideally situated for retaining walls less than 15 feet tall
- Can be used to build gravity walls up to 3' 4" high*, including the buried course
- Minimum outside radius, measured on the top course to the front of the units: 4 feet
- Minimum inside radius, measured on the base course to the front of the units: 6 feet

Cores align for easy filling



Lug locators for ease of alignment

SHAPES & SIZES

BLOCK



8 x 18 x 11½

CORNER



8 x 18 x 9

CAP



4 x 18 / 12 x 13

**Gravity wall heights are based on project specific conditions and may be lower than this value.
Check with your local Belgard Representative for product availability and color options.*



For more info, visit BelgardCommercial.com

Oldcastle APG - A CRH Company
400 Perimeter Center Terrace, Suite 1000
Atlanta, GA 30346
1-844-495-8210



© 2022 Oldcastle[®] APG, A CRH Company. All Rights Reserved.
BEL20-202 Rev: 6/16/2022