



AQUA-BRIC®

PERMEABLE PAVER


IDEAL FOR HEAVY DUTY
VEHICULAR APPLICATIONS AND
MACHINE-INSTALLED PROJECTS

FEATURES & BENEFITS


- Can eliminate stormwater runoff and improve water quality
- Meets the requirements of ASTM C936
- Smooth surface texture with a micro-chamfer to minimize vibration and enhance wheelchair comfort
- Can be utilized to construct an ADA-compliant pavement
- Innovative joint and void design optimizes structural performance
- False joint option (Type 4) provides a multi-size appearance
- Chamfer Width: 3 mm
- Joint Width: 5 mm
- Maintenance Void: 9 mm
- Surface Infiltration Rate: > 500 inches per hour (varies based on joint infill gradation)
- Surface Open Area: 9%

Belgard permeable pavers can be used for a variety of different vehicular applications. Appropriate shape and thickness is based on project-specific conditions, including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard Representative when specifying products for vehicular applications


LAYING PATTERNS



1-PIECE BASKET WEAVE



1-PIECE HERRINGBONE PATTERN




1-PIECE RUNNING BOND PATTERN


Mechanical
Installation Available 

Contact your local Belgard® representative for details and mechanical availability.

PALLET LAYOUT



AQUA-BRIC TYPE 4 (MECHANICAL)



AQUA-BRIC (STACKED BOND)

Contact your local Belgard sales representative for available colors.

SHAPES & SIZES

AQUA-BRIC



5 x 10 x 3 1/8"

AQUA-BRIC HALF PAVER



5 x 5 x 3 1/8"

AQUA-BRIC TYPE 4 (MECHANICAL)



5 x 10 x 3 1/8"