



DIAMOND PRO[®] AIR

SMOOTH FACE

AN INNOVATIVE SQUARE-FOOT BLOCK DESIGN THAT MAXIMIZES INSTALLATION AND SHIPPING EFFICIENCIES

FEATURES & BENEFITS

- Can be installed as a gravity wall or geogrid-reinforced wall.
- Weighing only 54 lbs., this 1 square foot block maximizes installation and shipping efficiencies
- Front lug design produces a 9/16" per unit setback for a 4° system batter
- Cores align for easy filling
- Top course is placed upside down in order to increase capping efficiency
- Ideally situated for retaining walls up to 12 feet tall
- Can be used to build gravity walls up to 3' 4" high*, including the buried course
- Minimum outside radius, measured on the top course to the front of the units: 4 feet
- Minimum inside radius, measured on the base course to the front of the units: 6 feet

**Gravity wall heights are based on project specific conditions and may be lower than this value. Check with your local Belgard Representative for product availability and color options.*

SHAPES & SIZES

8 X 18 BLOCK



8" x 18" x 11.5"
203 x 457 x 292 mm

CORNER



6" x 18" x 9"
203 x 457 x 230 mm

UNIVERSAL CAP*



4" x 18" x 12"
100 x 457 x 304 mm



For more info, visit BelgardCommercial.com

CANADA WEST

British Columbia Alberta Manitoba Saskatchewan

For the most current product offering and technical references – go to www.BelgardCommercial.com



©2025 Oldcastle® APG, A CRH Company. All Rights Reserved.
BEL 25-001 DIAMOND AIR SMOOTH