



BACKED BY  
**ANCHOR**  
DIAMOND  
INDUSTRY EXPERTS



# DIAMOND<sup>®</sup> 9D

## RETAINING WALL

A LIGHTWEIGHT SOLUTION FOR SEGMENTAL RETAINING WALLS WITH A WEATHERED STONE LOOK

### FEATURES & BENEFITS

- All system components are standard-split in-line
- Rear lip locators easily establish a uniform wall batter
- A matching cap and corner completes the system
- Build gravity walls up to 3 feet high\*, including the buried course.
- Taller walls can be built using geosynthetic reinforcement when designed by a qualified engineer.
- Minimum outside radius, measured on the top course to the front of the units: 3 feet
- Minimum inside radius, measured on the base course to the front of the units: 6 feet
- The rear lip establishes a 1 1/8" setback for a 10.6 degree system batter

### SHAPES & SIZES

#### STRAIGHT FACE



6 x 17 3/4 x 9

#### VIRTUAL JOINT



6 x 17 3/4 x 12

#### CAP



3 x 17 1/4 / 10 5/8 x 9

#### CORNER



6 x 18 x 9

*\*Gravity wall heights are based on project specific conditions and may be lower than this value.  
Check with your local Belgard Representative for product availability and color options.*

**BELGARD  
COMMERCIAL**

For more info, visit [BelgardCommercial.com](http://BelgardCommercial.com)

Oldcastle APG - A CRH Company  
400 Perimeter Center Terrace, Suite 1000  
Atlanta, GA 30346  
1-844-495-8210



© 2022 Oldcastle<sup>®</sup> APG, A CRH Company. All Rights Reserved.  
BEL20-202 Rev: 7/12/2022